

SG01-Clone Lights

LED Grow Light Tube for Horticulture

SG Series

Muizlux SG-series LED clone light just the right amount of photons without stressing fragile seedlings and clones. 120-degrees of photon output combined with the 0%-100% dimming feature you are able to balance the light intensity while aiming the photons to ensure an even blanket of light resulting in uniform rooting.









Contact: Wenny Chen
Tel&Whatsapp&Wechat:+86 13376539965
Email:sales04@muizlux.com




Length with 60cm/90cm/120cm/150cm(24 " /36 " /48 " /59 ")

The Muizlux LED grow light tube offers a unique platform for single and multi-layer crop cultivation plant factories.

By positioning the LED grow light tube as close as possible towards the crops, all the produced light is steered in the crop in the most effective way.

The light intensity on the plant canopy can be determined by the distance to the crop, the number of light bars on the surface as well as by light output controls on the lamps itself. In this way you can optimize the PPFD needed light level on the crop to the growth stage of the plants.

The Muizlux LED grow light tube can be installed in a horizontal setup with each lamp parallel to each other and bridged by a cable as in most tradition grow light setups, but can also be directly interconnected to each other to generate a long line of light in the grow rack installations.



Key benefits

- · Better rooting quality.
- Improved/controlled stretching process.
- IP66 rated for easy watering and cleaning.
- Daisy Chain end to end making installation easier.
- Uniform light for even plant growth.
- Ready for multi-layer installation.


Specification		0.6m / 24inch	0.9m / 36inch	1.2m / 48inch	1.5m / 59inch		
Lumen output	µmol/s	18.0-20.7	28.0-32.2	36.0-41.4	48.0-55.2		
Power consumption	W	9	14	18	24		
Efficacy	µmol/J	2.0-2.3					
Power factor		>90% at full load					
Input Voltage		100-277V AC, 50/60Hz					
Light Distribution		120°					
Spectrum		Clone seedling specialty spectrum					
Ingress protection rating		IP66					
Lifetime(Driver and LED L90)	hrs	>50,000					
Certifications		FCC,CE,UKCA,PSE,ROHS					
Warranty		3 Year Standard					









Spectral Distribution








Customized Spectrum

PPFD



SG01-FR-1.2m-18W-SINGLE-PPFD

With regards to light distribution SG01 have opted for a wide beam120 degrees output. In this way you can easily obtain a perfect flat light level over bars, what makes the system also suitable for lower crop light levels.

Muizlux SG01 Clone light is engineered to deliver consistent levels of photosynthetic flux density(PPFD). SG01 deliver a superior seedling spectrum, specially tailored to promote quick rooting, overall plant health, and vigorous early growth in both stem cuttings and seedlings.

SG01-FR-1.2m-18W-GROUP-PPFD








Length with 60cm/90cm/120cm/150cm(24 " /36 " /48 " /59 ")

Application



Dimensions & Installation



Par No.	Weight/PC(KG)	QTY/CTN	Out Carton Size(mm)	N.W.(KG)	G.W.(KG)
SG01-60cm	0.18	30PCS	W255*H220*L650	5.4	6.0
SG01-90cm	0.23	30PCS	W255*H220*L950	6.9	7.5
SG01-120cm	0.29	30PCS	W255*H220*L1250	8.7	9.2
SG01-150cm	0.36	30PCS	W255*H220*L1550	10.8	12.0



Sunnypower New Energy Co., Ltd.

4 Building, Caifa Industrial Zone, 181# Renmin Road, Fucheng Town, Longhua District, Shenzhen City, Guangdong Province, China



