

SR03-240W

LED PhotonPanel for Horticulture

SR Series

Muizlux LED PhotonPanel are ideal for commercial growers and home growers growing on vertical shelves. It has a wide-angle footprint and a targeted optimized full spectrum and various installation methods, which can fully meet the light supplementation needs of indoor planted seedlings, propagation, growth, harvesting harvesting and other stages.











10 YEARS HORTICULTURAL LIGHTING

SR03 LED PhotonPanel



Muzilux SR series Lighting's PhotonPanel is an innovative LED grow light panel, providing high intensity light for a wide range of horticultural applications. The common footprint size, along with its very thin profile, allows for versatile integration into vertical shelving units or grow tents.

By adjusting the light intensity and spectral distribution it is possible to control the growth of the plant. Thereby, production can be adapted to market demand.

The flexibility of the fixture means that cultures can be grown even if they are off-season.

The ultra-slim design ensures the full utilization of space, and due to very little emission of heat, the fixtures can be placed close to the plant.

The composition of the diode colors is adapted to the plant's needs (the photosynthetically active light), for improved growth.

LEDs do not emit much heat. The advantage is that by heating from an alternative heat source instead of the fixtures a healthy and uniform climate is ensured with- out large fluctuations in temperature.

Uniform light on the plant due to an optical lens system - thereby minimizing light waste and shadow footprint.

LED may reduce the need for Plant Growth Regula- tion (PGR).

Long lifetime with no reduction of light output over time.

With its long lifetime, many applications and improved plant growth, the choice of our LED fixture is a solid and future-proof investment.



Key benefits

- Adjustable spectral distribution and light intensity - can therefore be adapted to the individual culture's needs.
- Emits very little heat, so no need for cooling.
- Latest diode technology, which provides low power consumption, increased efficiency and long lifetime.
- Designed for the humid climate of a growing environment - IP65.
- LED improves plant growth and increases the taste intensity of edible plants.
- High-reflectance pure white soldermask for improved system efficacy.

Specification		L656mm×W480mm×H77mm / 25.8inch×18.9inch×3.3inch		
Photon Flux	µmol/s	648		
Power consumption	W	240		
System efficacy	µmol/J	2.7		
Power factor		>92% at full load		
Input Voltage		100-277V AC, 50/60Hz		
Light Distribution		120°		
Mounting Height		≥6" (15.2cm) Above Canopy		
Ingress protection rating		IP65		
Lifetime(Driver and LED L90)	hrs	>36,000		
Certifications		FCC,CE,UKCA,PSE,ROHS		
Warranty		3 years		

CO* = Intelligent control output










SR03 LED PhotonPanel



Spectral Distribution











Control System

PPFD

SR03-RO-240W-PPFD



SR03 Coverage








SR03 LED PhotonPanel



Dimensions & Package



Par No.	Inner Box Size(mm)	Weight/PC(KG)	QTY/CTN	Out Carton Size(mm)	N.W.(KG)	G.W.(KG)
SR03-240W	W530*H390*L140	4.95	4PCS	W550*H410*L590	19.8	21.2



Sunnypower New Energy Co., Ltd.

4 Building, Caifa Industrial Zone,181# Renmin Road, Fucheng Town, Longhua District, Shenzhen City, Guangdong Province, China



